

# SCAG POWER EQUIPMENT

## SERVICE INFORMATION SHEET 4

### CUTTING HEIGHT SPECIFICATIONS FOR SW AND SWZ WALK-BEHINDS

		DECK MOUNTED IN TOP HOLE					
CASTER SPACERS BELOW SUPPORT	NUMBER OF SPACERS ABOVE BLADES						
		0	1	2	3	4	5
	0	2-7/8	2-5/8	2-3/8	2-1/8	1-7/8	1-5/8
	1	3	2-3/4	2-1/2	1-1/4	2	1-3/4
	2	3-1/8	2-7/8	2-5/8	2-3/8	2-1/8	1-7/8
	3	3-1/4	3	2-3/4	2-1/2	2-1/4	2
	4	3-3/8	3-1/8	2-7/8	2-5/8	2-3/8	2-1/8
		DECK MOUNTED IN MIDDLE HOLE					
CASTER SPACERS BELOW SUPPORT	NUMBER OF SPACERS ABOVE BLADES						
		0	1	2	3	4	5
	0	3-1/8	2-7/8	2-5/8	2-3/8	2-1/8	1-7/8
	1	3-1/4	3	2-3/4	2-1/2	2-1/4	2
	2	3-1/2	3-1/4	3	2-3/4	2-1/2	2-1/4
	3	3-7/8	3-5/8	3-3/8	3-1/8	2-7/8	2-5/8
	4	4	3-3/4	3-1/2	3-1/4	3	2-3/4
		DECK MOUNTED IN BOTTOM HOLE					
CASTER SPACERS BELOW SUPPORT	NUMBER OF SPACERS ABOVE BLADES						
		0	1	2	3	4	5
	0	3-1/8	2-7/8	2-5/8	2-3/8	2-1/8	1-7/8
	1	3-1/2	3-1/4	3	2-3/4	2-1/2	2-1/4
	2	3-7/8	3-5/8	3-3/8	3-1/8	2-7/8	2-5/8
	3	4-1/4	4	3-3/4	3-1/2	3-1/4	3
	4	4-3/8	4-1/8	3-7/8	3-5/8	3-3/8	3-1/8

Recommended cutting position  
 The cutting height is computed for a 52" deck. Specifications for other size decks may vary slightly.