SCAG POWER EQUIPMENT

SERVICE INFORMATION SHEET 205

Hydraulic Oil Change Interval Chart

Please reference specific model information below for recommended hydraulic drive system oil, system capacity, hydraulic filter p/n and hydraulic oil change intervals.

Model	Oil Recommendation	Total Capacity	Initial Change	Subsequently	Hyd. Filter P/N
STT / STTII	SCAG 20W-50 Hyd. Oil	3.6 Qts	100 Hours	500 Hours*	48758
SCZ / SCZII 61" & 72"	SCAG 20W-50 Hyd. Oil	10 Qts	100 Hours	500 Hours*	HG71943
SCZ 48" & 52"	SCAG 20W-50 Hyd Oil	5 Qts	100 Hours	400 Hours*	HG52114
STC / STCII	SCAG 20W-50 Hyd. Oil	3.6 Qts	100 Hours	500 Hours*	48462-01
SPZ	SCAG 20W-50 Hyd. Oil	5 Qts	100 Hours	400 Hours*	HG52114
SFZ	SCAG 20W-50 Hyd. Oil	5 Qts	100 Hours	400 Hours*	HG52114
SZL	SCAG 20W-50 Hyd. Oil	5 Qts	100 Hours	400 Hours*	HG52114
SVR / SVRII	SCAG 20W-50 Hyd. Oil	3.6 Qts	100 Hours	500 Hours*	48462-01
SWZ	SCAG 20W-50 Hyd. Oil	3.6 Qts	100 Hours	500 Hours*	48462-01
SWZT	SCAG 20W-50 Hyd. Oil	5 Qts	100 Hours	400 Hours*	HG52114
WS	SCAG 20W-50 Hyd. Oil	3.6 Qts	100 Hours	500 Hours*	48462-01

*Subsequent hydraulic system service should be performed per hours indicated above or annually whichever occurs first.

Note: All capacities are approximate. Oil level should be checked as described in the hydraulic oil change procedure provided in the machine operators manual.

Hydraulic Drive System Oil	Part Number	
SCAG Hydraulic System Oil 20W-50 Qt.	486255	
SCAG Hydraulic System Oil 20W-50 Gal.	486254	